



NOTES :

- 1 - CONTACT MATERIAL : CARBON STEEL, 304 STAINLESS STEEL OR 316 STAINLESS STEEL
- 2 - VIBRATOR MOTOR TO BE 1750 RPM, 230 - 460/3/60, 1 1/2 HP.
- 3 - ALL ELECTRICAL CONNECTIONS TO BE FLEXIBLE.
- 4 - ALL CONNECTIONS TO BIN ACTIVATOR TO BE FLEXIBLE.

MODEL NO.	CAPACITY CU.FT.	"B"	"H"	"G"	"OH"
LBB 4-50	50	42"	88 1/4"	—	88 1/4"
LBB 4-75	75	47"	93 1/4"	19"	112 1/4"
LBB 4-100	100	47"	93 1/4"	40"	133 1/4"

NEOPRENE COVERED CABLE  
(SO 14/4) APPROX. 6 FT. LG.  
SUPPLIED BY V.S.

THE RECIPIENT OF THIS DOCUMENT AGREES NOT TO REPRODUCE, COPY, TRANSMIT OR USE THIS DOCUMENT AND/OR THE INFORMATION CONTAINED IN THIS DOCUMENT IN WHOLE OR IN PART, FOR ANY PURPOSE, EXCEPT WITH THE WRITTEN PERMISSION OF VIBRA SCREW INCORPORATED.

DO NOT SCALE PRINT  
UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN INCHES  
TOLERANCES:  
.XX = ±.01  
.XXX = ±.005  
FRACTIONAL = ±1/32"  
ANGULAR = ±1/2"  
BREAK SHARP EDGES .005-.015  
ALL SMALL FILLETS .020-.040R.

**Vibra Screw Incorporated**  
755 Union Blvd. Totowa, N.J. 07812-2207

TITLE 4 - 50 TO 100 LIVE BOTTOM BIN  
CENTER FLAT STOCK CROSSMEMBER  
AND GREASED VIBRATOR

SCALE 1=12  
CAD FILE NAME LBB /STDASSY/17950DSD

DWG. NO. 17950D-SD  
REV. NO. 1

1	WEBSITE DRAWING	MJM 4/26/06			
REV.	DESCRIPTION	DWN. BY DATE	CHK. BY DATE	APP. BY DATE	ELEC. APP. DATE