



- 1 - CONTACT MATERIAL: CARBON STEEL, 304 STL.STL. OR 316 STL.STL.
- 2 - D.C.MOTOR, 1/3 HP, 90 VA, BALDOR OR EQUAL,
- 3 - SPEED REDUCER: OHIO GEAR, MODEL. 2175, 60:1 RATIO OR EQUAL.
- 4 - BIN VIBRATOR, 1/4 HP, 460/3/60, 1800 RPM, TENV.

THE RECIPIENT OF THIS DOCUMENT AGREES NOT TO REPRODUCE, COPY, TRANSMIT OR USE THIS DOCUMENT AND/OR THE INFORMATION CONTAINED IN THIS DOCUMENT IN WHOLE OR IN PART FOR ANY REASON EXCEPT WITH THE WRITTEN PERMISSION OF VIBRA SCREW INCORPORATED.

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

TOLERANCES : .xx = ±.01
 .xxx = ±.005
 FRACTIONAL = ±1/32
 ANGULAR = ±1/2°

REMOVE ALL BURRS
 BREAK SHARP EDGES .005-.015
 ALL SMALL FILLETS .020-.040R.
 ALL FINISHED SURFACES TO BE 63-125 MICRO INCHES

Vibra Screw Incorporated
 755 UNION BLVD. TOTOWA, N.J. 07812

BELT FEEDER BF-75
 WITH 7" WIDE BELT & 5 CU.FT. BIN

SCALE 1/8" = 1"
 CUB FILE NAME FEEDER/BF/17956_REV1
 Dwg. No. C-17956

REV.	DESCRIPTION	DES. BY DATE	CHK. BY DATE	APP. BY DATE	BLD. APP. DATE
1	RELEASED FOR STANDARD	M.W. 5/18/06			