



MODEL NO.	CAPACITY CU.FT.	"B"	"H"	"G"	"OH"
LBB 6-200	200	47"	112 1/2"	31"	143 1/2"
LBB 6-250	250	47"	112 1/2"	49"	161 1/2"
LBB 6-300	300	47"	112 1/2"	69"	181 1/2"

NEOPRENE COVERED
CABLE (SD 14/4)
APPROX. 6FT. LG.

NOTES:

- 1 - CONTACT MATERIAL : C.S. ,304 SS OR 316 SS
- 2 - GYRATOR MOTOR TO BE 3 HP,230- 460 /3/60, 1750 RPM, TEFC
- 3 - ALL ELECTRICAL CONNECTIONS TO BE FLEXIBLE.
- 4 - ALL CONNECTIONS TO LIVE BOTTOM BIN TO BE FLEXIBLE.

6K GYRATOR
ASSY. SEE
NOTES 2 & 3

THE RECIPIENT OF THIS DOCUMENT AGREES NOT TO REPRODUCE, COPY, TRANSMIT OR USE THIS DOCUMENT AND/OR THE INFORMATION CONTAINED IN THIS DOCUMENT IN WHOLE OR IN PART, FOR ANY PURPOSE, EXCEPT WITH THE WRITTEN PERMISSION OF VIBRA SCREW INCORPORATED.

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES

TOLERANCES:
.XX = ±.01
.XXX = ±.005
FRACTIONAL = ±1/32"
ANGULAR = ±1/2"
BREAK SHARP EDGES .005-.015
ALL SMALL FILLETS .020-.040R.



Vibra Screw Incorporated
755 Union Blvd. Totowa, N.J. 07512-2207

TITLE 6-200 TO 300 LIVE BOTTOM BIN
CENTER FLAT STOCK CROSSMEMBER
AND 6K GYRATOR

SCALE .75=12 DWG. NO. 17991-SD 1
CAD FILE NAME LBB\ASSY\17991-SD_6FT_CFS_100_300_6K

1	WEBSITE DRAWING	MJM			
		6/29/01			
REV.	DESCRIPTION	DWN. BY DATE	CHK. BY DATE	APP. BY DATE	ELEC. APP. DATE