


NOTES:

- 1 - CONTACT MATERIAL: 304 STAINLES STEEL.
- 2 - GEAR MOTOR TO BE: 1/4 HP, 230-460/3/60.40.7 RPM.
- 3 - VIBRATOR MOTOR ,1/2 HP, #VE3 18/900, 460/3/60.
- 4 - ALL CONNECTIONS TO BE FLEXIBLE.
- 5 - ALL CONNECTIONS TO TROUGH TO BE FLEXIBLE.

THE RECIPIENT OF THIS DOCUMENT AGREES NOT TO REPRODUCE, COPY, TRANSMIT OR USE THIS DOCUMENT AND/OR THE INFORMATION CONTAINED IN THIS DOCUMENT IN WHOLE OR IN PART, FOR ANY PURPOSE, EXCEPT WITH THE WRITTEN PERMISSION OF VIBRA SCREW INCORPORATED.

DO NOT SCALE PRINT		 <b>Vibra Screw Incorporated</b> 755 UNION BLVD. TOTOWA, N.J. 07512	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		TITLE <b>VIBRA BLENDER MODEL I</b>	
TOLERANCES: .XX = ±.01 .XXX = ±.005 FRACTIONAL = ±1/32" ANGULAR = ±1/2" BREAK SHARP EDGES .005-.015 ALL SMALL FILLETS .020-.040R.		SCALE 3/16=1	DWG. NO. <b>VB-C-18076</b>
CAD FILE NAME BLENDER\1\18076		REV. NO. <b>1</b>	

1	RELEASED FOR STANDARD	MJM			
		5/30/06			
REV.	DESCRIPTION	DWN. BY DATE	CHK. BY DATE	APP. BY DATE	