


- NOTES:
 1 - CONTACT MATERIAL: C.STL., 304 STL.STL. OR 316 STL.STL.
 2 - GYRATOR MOTOR: 1 HP, TENV, 230-460/3/60, 1750 RPM.
 3 - ALL ELECTRICAL CONNECTIONS TO BE FLEXIBLE.
 4 - GEAR MOTOR 3/4 HP, TEFC, 230-460/3/60, 30 RPM SM CYCLO, 59 RATID.
 5 - ALL CONNECTION TO VIBRA BLENDER TO BE FLEXIBLE.

THE RECIPIENT OF THIS DOCUMENT AGREES NOT TO REPRODUCE, COPY, TRANSMIT OR USE THIS DOCUMENT AND/OR THE INFORMATION CONTAINED IN THIS DOCUMENT IN WHOLE OR IN PART, FOR ANY PURPOSE, EXCEPT WITH THE WRITTEN PERMISSION OF VIBRA SCREW INCORPORATED.

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
 TOLERANCES:
 .XX = ±.01
 .XXX = ±.005
 FRACTIONAL = ±1/32"
 ANGULAR = ±1/2"
 BREAK SHARP EDGES .005-.015
 ALL SMALL FILLETS .020-.040R.

 Vibra Screw Incorporated 755 UNION BLVD. TOTOWA, N.J. 07072	
TITLE VIBRA BLENDER MODEL II	
SCALE 1/8"=1"	DWG. NO. VB-C-18077
CAD FILE NAME VIBRABLENDER_MODEL2_18077	REV. NO. 1

1	RELEASED FOR STANDARD	MJM			
		5/31/06			
REV.	DESCRIPTION	DWN. BY DATE	CHK. BY DATE	APP. BY DATE	