



| APPLICATION DATA | |
|------------------|------------------|
| MATERIAL | ACTIVATED CARBON |
| BULK DENSITY | 32 PPM |
| FLOW RATE | 100-600 PPH |
| MOISTURE | NIL |
| TEMPERATURE | AMBIENT |
| PRESSURE | ATMOSPHERIC |
| PARTICLE SIZE | POWDER |

| REV. | DESCRIPTION | DATE | CHK. BY | APP. BY |
|------|---------------------------|---------|---------|---------|
| 0 | RELEASED FOR FABRICATION | 3/29/08 | MM | MM |
| C | ADDED 3\"/> | 3/29/08 | MM | MM |
| B | REV. PER CUSTOMER CHANGES | 3/19/08 | MM | MM |
| A | RELEASED FOR APPROVAL | 2/19/08 | MM | MM |

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES

TOLERANCES:
XX = ±.01
XXX = ±.005/±.02
FIN. ANGULAR = ±1/2°
BREAK SHARP EDGES .005-.015
ALL SMALL FILLETS .020-.040R
ALL FIN. SURF. FIN. 32
ALL FIN. MICRO INCHES 63-120

SCALE: 3/4"=1'

CD FILE NAME: 200801SVS.2008121

REV. NO. 0

AS-D-2008121

Vibra Screw Incorporated
755 UNION BLVD. TORONTO, N.I. 07512
LW SYSTEM 2-20000-250
FOR: GE BER

NOTES FOR 6-250 LBB # 2008121

- CONTACT MATERIAL: CARBON STEEL
- VIBRATOR MOTOR TO BE 2 1/2 HP, 460/3/60, 1800 RPM
- ALL ELECTRICAL CONNECTIONS TO BE FLEXIBLE, FLEXIBLE
- ALL CARBON STEEL SURFACES SANDBLASTED AND PAINTED EXTERIOR ONLY WITH BLUE EPOXY, INTERIOR COATED WITH VEGETABLE OIL.

NOTES FOR 1 1/2" VERSI FEEDER # 2008122

- CONTACT MATERIAL: CARBON STEEL
- INVERTER DUTY MOTOR 3/4 HP, 460/3/60 TEN, 56 C FRAME, MOD. # 10NM3542.
- SPEED REDUCER: OHIO GEAR, BWO-2175, 10:1 RATIO.
- VIBRATOR MOTOR TO BE 1 1/4 HP, MODEL VE 3 36/120, 460/3/60 ONLY WITH BLUE EPOXY, INTERIOR COATED WITH VEGETABLE OIL.
- 2 FLIGHT SCREW W/TUBE SHIP LOOSE.

NOTES FOR BIN VENT MODEL 100 # 2008123

- CONTACT MATERIAL TO BE CARBON STEEL.
- FILTER AREA 100 SQUARE FEET AIR TO MEDIA RATIO 2:1.
- DESIGN CONDITION: 200 CFM @ 1" WG, 70° F.
- FILTER SHAKER MOTOR, 1/4 HP, TEN, 1175 RPM, 460/3/60.
- PLATING CONTACT MOTOR, 1/2 HP, TEN, 1175 RPM, 460/3/60.
- FRANSPORTER MOTOR, 1/2 HP, TEN, 1175 RPM, 460/3/60.
- ACTIVATION OF SHAKER MOTOR AND NEVA 12 ENCLOSURE WITH START AND CLEAN PUSHBUTTONS.
- FAN MOTOR, 1 HP, TECO, 3450 RPM, 460/3/60.
- WETHER BEND ROOF FOR OUTDOOR INSTALLATION.

THE SIGNATURE OF THIS DOCUMENT AGREE NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION CONTAINED IN THIS DOCUMENT IN WHOLE OR IN PART, FOR ANY PURPOSES, EXCEPT WITH THE WRITTEN PERMISSION OF VIBRA SCREW INCORPORATED.