



NEOPRENE COVERED CABLE (SO 14/4) APPROX. 6 FT. LG. SUPPLIED BY V.S.

VS 6K GYRATOR (SEE NOTES 2 & 3)

NOTES:

- 1 - CONTACT MATERIAL: CARBON STEEL, 304 STAINLESS STL., OR 316 STAINLESS STEEL.
- 2 - GYRATOR MOTOR TO BE 3HP, 1750 RPM, TENV, OR EXPL. PF., 230 OR 460/3/60.
- 3 - ALL ELECTRICAL CONNECTIONS TO BE FLEXIBLE.
- 4 - ALL CONNECTIONS TO BIN ACTIVATOR TO BE FLEXIBLE.

"A" OUTLET SIZE	"C" OVERALL HEIGHT
8"	52 1/4"
10"	51 1/4"
12"	50 1/4"
14"	49 1/4"

THE RECIPIENT OF THIS DOCUMENT AGREES NOT TO REPRODUCE, COPY, TRANSMIT OR USE THIS DOCUMENT AND/OR THE INFORMATION CONTAINED IN THIS DOCUMENT IN WHOLE OR IN PART, FOR ANY PURPOSE, EXCEPT WITH THE WRITTEN PERMISSION OF VIBRA SCREW INCORPORATED.

*Vibra Screw Incorporated*  
 755 UNION BLVD. TOTOWA, N.J. 07512

TITLE 8'-0" DIA. BIN ACTIVATOR WITH PREASSEMBLED MOUNTING RING AND OIL LUBRICATED GYRATOR

DWN/DATE I.S. 5/02/2001	CHK. BY	DWG. NO.
CAD FILE NAME N:\BA\STDASSY\15323-SD	APP. BY	15323-SD