



- NOTES :
- 1 - CONTACT MATERIAL : CARBON STEEL, 304 STAINLESS STEEL OR 316 STAINLESS STEEL
  - 2 - VIBRATOR MOTOR TO BE 1750 RPM, 230 - 460/3/60, 1 1/2 HP.
  - 3 - ALL ELECTRICAL CONNECTIONS TO BE FLEXIBLE.
  - 4 - ALL CONNECTIONS TO BIN ACTIVATOR TO BE FLEXIBLE.

MODEL NO.	CAPACITY CU.FT.	"B"	"H"	"G"	"OH"
LBB 4-50	50	42"	88 1/4"	—	88 1/4"
LBB 4-75	75	47"	93 1/4"	19"	112 1/4"
LBB 4-100	100	47"	93 1/4"	40"	133 1/4"

NEOPRENE COVERED CABLE  
(SO 14/4) APPROX. 6 FT. LG.  
SUPPLIED BY V.S.

THE RECIPIENT OF THIS DOCUMENT AGREES NOT TO REPRODUCE, COPY, TRANSMIT OR USE THIS DOCUMENT AND/OR THE INFORMATION CONTAINED IN THIS DOCUMENT IN WHOLE OR IN PART, FOR ANY PURPOSE, EXCEPT WITH THE WRITTEN PERMISSION OF VIBRA SCREW INCORPORATED.

1	WEBSITE DRAWING	MJM			
		4/26/06			
REV.	DESCRIPTION	DWN. BY DATE	CHK. BY DATE	APP. BY DATE	ELEC. APP. DATE

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

TOLERANCES:  
.XX = ±.01  
.XXX = ±.005  
FRACTIONAL = ±1/32"  
ANGULAR = ±1/2"

BREAK SHARP EDGES .005-.015  
ALL SMALL FILLETS .020-.040R.

**Vibra Screw Incorporated**  
755 Union Blvd. Totowa, N.J. 07812-2207

TITLE 4 - 50 TO 100 LIVE BOTTOM BIN  
CENTER FLAT STOCK CROSSMEMBER  
AND GREASED VIBRATOR

SCALE 1=12  
CAD FILE NAME LBB /STDASSY/17950DSD

DWG. NO. 17950D-SD  
REV. NO. 1