



DASH No.	A OD	C
-1	8 OD	22 3/8
-2	10 OD	21 3/8
-3	12 OD	20 3/8

**NOTES -**

- 1 - CONTACT MATERIAL - CARBON STEEL, 304 SS, 316 SS
- 2 - VIBRATOR MOTOR - 0.62 HP, 230- 460/3/60, 1800 RPM
- 3 - ALL ELECTRICAL CONNECTIONS TO BE FLEXIBLE
- 4 - ALL CONNECTIONS TO BIN ACTIVATOR MUST BE FLEXIBLE

THE RECIPIENT OF THIS DOCUMENT AGREES NOT TO REPRODUCE, COPY, TRANSMIT OR USE THIS DOCUMENT AND/OR THE INFORMATION CONTAINED IN THIS DOCUMENT IN WHOLE OR IN PART, FOR ANY PURPOSE, EXCEPT WITH THE WRITTEN PERMISSION OF VIBRA SCREW INCORPORATED.

DO NOT SCALE PRINT		<b>Vibra Screw Incorporated</b> 755 Union Blvd. Totowa, N.J. 07512-2207	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		TITLE <b>2'-0" DIA. BIN ACTIVATOR FLAT STOCK CROSS MEMBER DESIGN AND GREASED VIBRATOR</b>	
TOLERANCES: .XX = ±.01 .XXX = ±.005 FRACTIONAL = ±1/32" ANGULAR = ±1/2"		SCALE <b>3/16"=1"</b>	DWG. NO. <b>17955-SD</b>
BREAK SHARP EDGES .005-.015 ALL SMALL FILLETS .020-.040R. ALL FINISHED SURFACES 63-125 MICRO INCHES		CAD FILE NAME n:\bo\stdossy\17955-SD	REV. NO. <b>0</b>

0	RELEASED FOR REFERENCE ONLY	L.K. 5/14/01			
REV.	DESCRIPTION	DATE	CHK. BY DATE	APP. BY DATE	ELEC. APP. DATE