





"A" O.D.	"C"
8" O.D.	24 3/8"
10" O.D.	23 3/8"
12" O.D.	22 3/8"

- NEOPRENE COVERED CABLE (SOO 16/4) APPROX. 6'-0' LG. SUPPLIED BY V.S.

THE RECIPIENT OF THIS DOCUMENT AGREES NOT TO REPRO-DUCE, COPY, TRANSMIT OR USE THIS DOCUMENT AND/OR THE INFORMATION CONTAINED IN THIS DOCUMENT IN WHOLE OR IN PART, FOR ANY PURPOSE, EXCEPT WITH THE WRITTEN PERMISSION OF VIBRA SCREW INCORPORATED.

NOTES:

- 1 CONTACT MATERIAL: CARBON STEEL, 304 S/S, 316 S/S.
- 2 VIBRATOR DRIVE TO BE: 0.62 HP, T.E.N.V., 1750 RPM, 230-460/3/60.
- 3 ALL ELECTRICAL CONNECTIONS TO BE FLEXIBLE

╼l o.d. l╾

4 - ALL CONNECTIONS TO BIN DISCHARGER MUST BE FLEXIBLE

Vibra Screw Incorporated

755 Union Blvd.

Totowa, N.J. 07512-2207

DISCHARGER CENTER FLAT STOCK AND GREASED VIBRATOR

DWN / DATE: MJM 8/21/01	
CAD FILE NAME	
N: \BA\BD\STDASSY\17972-SD	

17972 - SD

REV. NO.