



NOTES -

- 1 - CONTACT MATERIAL - CARBON STEEL, 304 SS, 316 SS
- 2 - GYRATOR MOTOR - 2 HP, 1750 RPM, TEFC, 230-460/3/60.
- 3 - ALL ELECTRICAL CONNECTIONS TO BE FLEXIBLE
- 4 - ALL CONNECTIONS TO BIN ACTIVATOR MUST BE FLEXIBLE

DASH No.	A OD	C
-1	8 OD	30 1/4
-2	10 OD	29 1/4
-3	12 OD	28 1/4

THE RECIPIENT OF THIS DOCUMENT AGREES NOT TO REPRODUCE, COPY, TRANSMIT OR USE THIS DOCUMENT AND/OR THE INFORMATION CONTAINED IN THIS DOCUMENT IN WHOLE OR IN PART, FOR ANY PURPOSE, EXCEPT WITH THE WRITTEN PERMISSION OF VIBRA SCREW INCORPORATED.

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN INCHES

TOLERANCES:  
.XX = ±.01  
.XXX = ±.005  
FRACTIONAL = ±1/32"  
ANGULAR = ±1/2"  
BREAK SHARP EDGES .005-.015  
ALL SMALL FILLETS .020-.040R.  
ALL FINISHED SURFACES 63-125  
MICRO INCHES



Vibra Screw Incorporated  
755 Union Blvd. Totowa, N.J. 07512-2207

TITLE 4'-0" DIA. BIN ACTIVATOR  
CENTER FLAT STOCK CROSS MEMBER  
AND 3K GYRATOR

SCALE 1/8" = 1"

DWG. NO. 17984-SD  
REV. NO. 0

CAD FILE NAME  
bo\atdossy\17984-SD\_4ft\_3k\_center\_flat\_stock

0	RELEASED FOR REFERENCE ONLY	MJM 8/24/01			
REV.	DESCRIPTION	DWN. BY DATE	CHK. BY DATE	APP. BY DATE	ELEC. APP. DATE