



NOTES -

1. CONTACT MATERIAL - POLYETHYLENE, SCREW & TUBE - 304 SS
2. DRIVE MOTOR - 1/2 HP, TENV, 1750 RPM, 90 VA PERMANENT MAGNET DC MOTOR, 56 C-FACE, BALDOR No. CDP-3330 OR EQUAL
3. SPEED REDUCER - MODEL #B-MQ-2175, 10:1 RATIO
4. CONTROLLER - AVAILABLE IN BOTH BATCH AND CONTINUOUS OPERATION
5. VIBRATOR - MODEL No. VBM-2/M, 3600 RPM, 115V/1/60HZ.
6. CARBON STEEL SURFACES TO BE SANDBLASTED AND PAINTED WITH WHITE ENAMEL, 2-3 MILS DFT.

MATERIAL : VARIOUS MATERIALS
 BULK DENSITY : CUSTOMER TO ADVISE
 FLOW RATE : CUSTOMER TO ADVISE
 MOISTURE : NIL
 TEMPERATURE : AMBIENT
 PRESSURE : ATMOSPHERIC
 PARTICLE SIZE : CUSTOMER TO SPECIFY

THE RECIPIENT OF THIS DOCUMENT AGREES NOT TO REPRODUCE, COPY, TRANSMIT OR USE THIS DOCUMENT AND/OR THE INFORMATION CONTAINED IN THIS DOCUMENT IN WHOLE OR IN PART, FOR ANY PURPOSE, EXCEPT WITH THE WRITTEN PERMISSION OF VIBRA SCREW INCORPORATED.

DO NOT SCALE PRINT		Vibra Screw Incorporated 755 Union Blvd. Totowa, N.J. 07812-2207	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		TITLE 1 1/2" AccuFeed FEEDER (MODEL: LIW 1.5-500-1.5)	
TOLERANCES: .XX = ±.01 .XXX = ±.005 FRACTIONAL = ±1/32" ANGULAR = ±1/2"		SCALE 1/4" = 1"	DWG. NO. SD-18026
BREAK SHARP EDGES .005-.015 ALL SMALL FILLETS .020-.040R. ALL FINISHED SURFACES 63-125 MICRO INCHES		CAD FILE NAME SALES\ACAD\SD-18026	REV. NO. SD

SD	RELEASED FOR STANDARD DWG.	HF	07/16/03		
REV.	DESCRIPTION	DWN. BY	CHK. BY	APP. BY	ELEC. APP. DATE