



NOTES:

- 1 - CONTACT MATERIAL : CARBON STEEL, 304 STL.STL. OR 316 STL.STL.
- 2 - GYRATOR MOTOR: 2 HP, TENV, 460/3/60, 1750 RPM.
- 3 - GEAR MOTOR , 2 HP, 1750 RPM, TEFC, 145 TC FRAME , 460/3/60  
25 : 1 RATIO, C- FACE INPUT HORIZONTAL REDUCER,
- 4 - ALL CONNECTION TO MOTOR MUST BE FLEXIBLE.
- 5 - ALL CONNECTION TO VIBRA BLENDER MUST BE FLEXIBLE.

THE RECIPIENT OF THIS DOCUMENT AGREES NOT TO REPRODUCE, COPY, TRANSMIT OR USE THIS DOCUMENT AND/OR THE INFORMATION CONTAINED IN THIS DOCUMENT IN WHOLE OR IN PART, FOR ANY PURPOSE, EXCEPT WITH THE WRITTEN PERMISSION OF VIBRA SCREW INCORPORATED.

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

TOLERANCES:  
 .XX = ±.01  
 .XXX = ±.005  
 FRACTIONAL = ±1/32"  
 ANGULAR = ±1/2"  
 BREAK SHARP EDGES .005-.015  
 ALL SMALL FILLETS .020-.040R.



**Vibra Screw Incorporated**  
 755 UNION BLVD. TOTOWA, N.J. 07512

TITLE  
**VIBRA BLENDER  
 MODEL III**

SCALE  
 1=12  
 CAD FILE NAME  
 BLENDER\MODEL III\18078

DWG. NO.  
**VB-C-18078**

REV. NO.  
**1**

1	RELEASED FOR STANDARD	MJM			
		5/31/06			
REV.	DESCRIPTION	DNW. BY DATE	CHK. BY DATE	APP. BY DATE	