



- NOTES FOR 1 1/2\"/>**

- NOTES FOR 185 GAL TANK # 2009146**

- NOTES FOR TORRIT BIN VENT # 2009148**

- NOTES FOR 4-120 SBB # 2009147**

- NOTES FOR BBU II-V-HD # 2009149**

| APPLICATION DATA | |
|------------------|---------------|
| MATERIAL: | HYDRATED LIME |
| BULK DENSITY: | 85 PCF |
| FLOW RATE: | 1.5 CU FT/HR |
| MOISTURE: | NIL |
| TEMPERATURE: | AMBIENT |
| PRESSURE: | ATMOSPHERIC |
| PARTICLE SIZE: | POWDER |

| REV. | DESCRIPTION | DATE | BY | CHKD. |
|------|--------------------------|-------|----|-------|
| 0 | RELEASED FOR FABRICATION | MM/YY | | |
| A | ADDED 2\"/> | | | |

Vibra Screw Incorporated
 755 Union Blvd.,
 Tokoma, N.J. 07512-2027

NEW LIME SYSTEM TRAIN #1

THE RECIPIENT OF THIS DOCUMENT AGREES NOT TO REPRODUCE, RESELL, RENT, LEASE, LOAN, COPY, OR TRANSMIT IN ANY MANNER THE INFORMATION CONTAINED HEREIN WITHOUT THE WRITTEN PERMISSION OF VIBRA SCREW INCORPORATED.

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

TOLERANCES: XX = ±.01
 XXX = ±.005
 FRACTIONAL = ±1/32"
 BREAK SHARP EDGES 1:65-015
 ALL SMALL FILLETS .020-.040"
 ALL FINISHED SURFACES 63-125 MICRO INCHES

SCALE: 3/4" = 1"
 DWG. NO. AS-D-2009145
 REV. NO. 1